

## RADIAGREEN OSD - Type 3 dispersant



<b>COMPOSITION</b>	Anionic surfactant, ethoxylates; 100% free of any aromatic hydrocarbon-based solvents; emulsifying agents compliant with AFNOR 90 348 test protocol
<b>VISCOSITY</b>	Ca. 31 mm <sup>2</sup> /s (40°C) or 25.5 Centistokes (ASTM D 445, at 40°C)
<b>FLASH POINT</b>	>110°C (ASTM D 92)
<b>CLOUD POINT</b>	-16°C (ASTM D 2500)
<b>POUR POINT</b>	-21°C (ASTM D 97)
<b>PH</b>	6.33 (ASTM D 1172)
<b>TOXICITY</b>	No acute toxicity (Category 4); may cause skin irritation (Category 2) and serious eye damage (Category 1); Hazard phrases: H302, H315, H318; Risk phrases: R22, R38, R41
<b>ECOTOXICITY</b>	Toxicity on white shrimp ( <i>Palaemonetes varians</i> ) less than 10 times the reference toxicity of Noramium (AFNOR 90 349)
<b>BIODEGRADABILITY</b>	>50% after 28 days (AFNOR 90 346)
<b>OTHER ECOLOGICAL INFORMATION</b>	According to literature: no environmental hazard; compliant with and passed the ecotoxicity and biodegradability 'Sea Test' and 'Rock Shore Test' protocols in UK; bioaccumulation potential (i.e. Log Pow) >5
<b>EFFICIENCY</b>	Compliant with requirements of the AFNOR NFT 90-345 (France) and WSL LR 448 (UK) test protocols, both in concentrated and in diluted form (dil. to 10 %). Its efficiency is not affected by the viscosity of the crude oil (ranging between 500 to 2000 mPa.s at 10°C)
<b>EU REGULATIONS</b>	No REACH Annex XVII restrictions; contains no REACH candidate substance

### PACKING AND TRANSPORT INFORMATION

<b>PACKING FORM</b>	Packed in Intermediate Bulk Container (IBC Schutz Ecobulk LX 1000) containing 950kg
<b>TRANSPORT INFORMATION</b>	Not subject to any transport regulations by air (IATA), sea (IMDG) or land (ADR, RID)

## APPROVAL FOR USE

The dispersant is approved for use in the following European states: Belgium, Croatia, Cyprus, France, Ireland, Malta, Netherlands, Portugal, Spain and United Kingdom.

## DIRECTIONS FOR USE

Radiagreen OSD can be used pure, undiluted, in a 1 on 20 proportions (1 part dispersant for 20 parts of oil) for dispersion by means of aircraft or vessel.

Appropriate spraying equipment is advisable such that the product is uniformly distributed on the surface of the spill. An additional mechanical mixing may be advisable to enhance the breaking.

Always make sure the dispersant is sprayed on top of the spill. Give the dispersant some time (30-40 minutes) to penetrate the oil. Then spread the treated spill using a mechanical device or a water jet (this might not be necessary in open sea).

## EMERGENCY CONTACT DETAILS

Emergency telephone number (24/7): +32 3 575 55 55 (SGS ERS; Oleon Contract No 76858)

Supplier information: OLEON N.V.  
Assenedestraat 2  
9940 Ertvelde - Belgium  
Telephone: +32 9 34110 11  
Fax: +32 9 34110 00  
Email: [sds@oleon.com](mailto:sds@oleon.com)

